



**TS2 Frame Grabber  
MODEL FGR 1000  
Rev 2.0**

1) The Unit referred to in this document shall include:

- TS2 Frame Grabber unit
- 24V Pigtail Power Cable
- SDLC Cable
- Memory Token
- Users Manual
- Software CD with FrameView software

Accessory Hardware to be provided with this Unit are specified in Section 2.

2) The Unit shall include the following accessories (check boxes below):

Extra Memory Token:  Qty: \_\_\_\_\_

Memory Token Reader:  Qty: \_\_\_\_\_

(Extra Memory Token Reader includes: Memory Token Reader, USB cable, FrameView software)

Mounting Brackets:

- 3) The Unit shall require a Microsoft Windows-based computer (PC) to run the FrameView software. The PC operating system must be Windows XP or Vista and include a HTML browser. The minimum PC hardware specification shall be Pentium (or equivalent) processor at 150 MHz, 32 MB RAM, 1.0 GB hard drive, 4X CDROM drive (for software installation), one USB port (for the Memory Token Reader), and 640 X 480 monitor resolution. NOTE: The PC for use with this Unit  IS  IS NOT a part of this equipment specification.
- 4) The FrameView software running on the PC shall provide the user interface for viewing the frame data, allowing the user to sort the frames in multiple ways and show only the suspect frames for quick review and troubleshooting.
- 5) The frame data shall be stored on the Memory Token in the occurrence of a transfer within the cabinet. A user accessible button shall also be provided on the Unit for the user to force the frame data to be written to the Memory Token. The frame data will be viewed using the FrameView software that is provided with the Unit or the Memory Token Reader.
- 6) The Unit shall include a Operating Manual describing all steps in the setup and operation of the Unit as well as unlimited telephone technical support for the purchasing agency or firm.
- 7) The Unit shall provide Help files to extend ease of use to novice or infrequent operators of the Unit.
- 8) The purchaser's interest in the Unit shall be protected by a one-year limited warranty on parts and labor. The continuing utility of the Unit shall be further protected by the availability of repair, update, calibration, and extended warranty services from the manufacturer.
- 9) Software and Firmware updates for the Unit shall be made available to download at no charge from the Internet ([www.atsi-tester.com](http://www.atsi-tester.com)).
- 10) The unit is shipped from the factory completely calibrated and tested. No further calibration should be required.